

TWENTY

With a thickness of 20mm, these tiles guarantee peace of mind for outdoor flooring solutions. Tough, resistant and durable, they are the perfect choice for high traffic areas in both residential and public environments. Available in the Oceanic 2.0, Fused and Mineral D collections, Twenty combines practicality with aesthetics for sophisticated urban living.

Grey **TW04ST** 600x600mm




Floor // Grey TW04ST 600x600mm


ROUGH AND STRONG SURFACE

The structured surface of Twenty is barely perceptible and underlines the defining characteristic of this collection, making it a perfect mix of aesthetic and functionality for outdoor applications and high traffic areas.


7 CAPTIVATING COLOURS



Grigio TW01ST




Nero TW02ST




Cream TW03ST




Grey TW04ST



Nera TW05ST



Dolomite TW06ST



Pirite TW07ST



Floor // Twenty Collection
- **TW01ST** 600x600mm

Features:



Applications:




Surface:

ST Structured

AVAILABLE COLOURS:



Grigio TW01ST




Nero TW02ST



Cream TW03ST



Grey TW04ST



Nera TW05ST



Dolomite TW06ST



Pirite TW07ST

SIZES:



- Grigio TW01ST
- Nero TW02ST
- Cream TW03ST
- Grey TW04ST
- Nera TW05ST
- Dolomite TW06ST
- Pirite TW07ST

TECHNICAL SPECIFICATION:

Type Of Test	Standard Test MS ISO13006	ISO Standard Requirement	Feruni
Dimensions & Surface Quality			
Length & Width	ISO 10545-2	± 0.6%	± 0.2%*
Thickness	ISO 10545-2	± 5.0%	± 5.0%
Straightness of Sides	ISO 10545-2	± 0.5%	± 0.2%
Rectangularity	ISO 10545-2	± 0.5%	± 0.2%
Surface Flatness	ISO 10545-2	± 0.5%	± 0.2%
	ISO 10545-2	± 0.5%	± 0.2%
	ISO 10545-2	± 0.5%	± 0.2%
Surface Quality	ISO 10545-2	≥95% free from visible defect	≥95% free from visible defect
Physical Properties			
Water Absorption	ISO 10545-3	Group BIa, E ≤ 0.5%	Group BIa, E ≤ 0.2%
Breaking Strength	ISO 10545-4	≥ 1300N	≥ 9000N
Modulus of Rupture	ISO 10545-4	Min. 35N/mm ²	Min. 38N/mm ²
Surface Abrasion (PEI)	ISO 10545-7	Test Method Available	Class 4
Thermal Shock	ISO 10545-9	No Visible Crack	No Visible Crack
Slipperiness	DIN 51130	R9 to R13	R10
Chemical Properties			
Chemical Resistance	ISO 10545-13	Minimum Class B	GA (V)
Stain Resistance	ISO 10545-14	Minimum Class 3	Minimum Class 3

PACKING LIST:

Sizes (mm)	PCS/CTN	CTN/PLT	M ² /CTN	KG/CTN	KG/PLT
600x600	2	36	0.72	35	1260

www.feruni.com

Feruni Ceramiche Sdn Bhd

No.12, Jalan 51A/213, Seksyen 51A, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia.

T: +603 7784 7277 F: +603 7784 7727 E: enquiry@feruni.com